



| Size | OD | Flange Thickness | ID | Bolt # | Bolt Hole Diameter | Bolt Circle | Unit Weight (lbs) |
|------|---------|------------------|---------|--------|--------------------|-------------|-------------------|
| 1" | 3.500" | 0.440" | 0.910" | 4 | 0.630" | 2.380" | 1.0 |
| 1 ¼" | 4.630" | 0.500" | 1.720" | 4 | 0.630" | 3.500" | 1.7 |
| 1 ½" | 5.000" | 0.500" | 1.970" | 4 | 0.630" | 3.880" | 2.0 |
| 2" | 6.000" | 0.500" | 2.750" | 4 | 0.750" | 4.750" | 3.0 |
| 3" | 7.500" | 0.500" | 3.560" | 4 | 0.750" | 6.000" | 4.5 |
| 4" | 9.000" | 0.560" | 4.560" | 8 | 0.750" | 7.500" | 6.5 |
| 6" | 11.000" | 0.630" | 6.750" | 8 | 0.880" | 9.500" | 8.5 |
| 8" | 13.500" | 0.630" | 8.750" | 8 | 0.880" | 11.750" | 12.0 |
| 10" | 16.000" | 0.630" | 10.880" | 12 | 1.000" | 14.250" | 16.0 |
| 12" | 19.000" | 0.750" | 12.880" | 12 | 1.000" | 17.000" | 27.0 |

Note Please contact a Rahn Customer Sales Rep for availability

Note Cast in Ductile Iron A536. Tensile: 80,000 psi Yield: 55,000 psi Elongation: 6%. Vital Dimensions AWWA C207. Mates with ANSI B16.5, B16.47; AWWA C207. Red oxide primer, hot dipped galvanized. DR 7



Rahn Plastics Incorporated
 54 Ferris Drive, North Bay
 Ontario, Canada P1A 4M3
www.rahnpastics.com

(Local) 1-705-495-6777
 (Toll Free) 1-888-433-0111
 (Fax) 1-866-495-6820